Movement detector switch from 40 to 300W/VA 230 V~ white Simon 75

REF. **75340-30**



BASIC INFORMATION

DESCRIPTION

Motion detector switch in white colour of the Simon 75 series with a power of 230 V and typology IR / Sound of 50-60 Hz. It has a timer for disconnection between 4 seconds and 10 minutes and is a switch suitable for flush mounting. It has an element and supports a cable section of 1.5 to 2.5 mm with a stripped 8 mm and it works perfectly in places with a temperature located between 0 to 35 ° C, although it is capable of withstanding temperatures of 20 to 70, approximately. Its design is the regulations UNE-EN -60669-2-1: 2005 + A1: 2010 + A12: 2011 and is made of electronic components with halogen-free thermoplastic insulation. Its clamping is screwed and its type of operation by detecting and also has a switch-off timer of between 4 seconds and 10 minutes and is suitable both for surface and flush mounting and can also, the installation of 2 units in parallel.

FINISH

White

COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature and Simon 82 frames

COMPATIBLE WITH MECHANICAL 2-WAY/CROSSOVER SWITCH

No

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

COMPATIBLE WITH MECHANICAL SWITCH

No

PACKAGING CONTENTS

Movement detector and instruction sheet

REMARKS

Allows 2 units to be installed in parallel.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

NUMBER OF CONTACTS
3

NUMBER OF CONTROLLABLE CIRCUITS
1

DISCONNECTION TIMER
4 seconds to 10 minutes

COMPATIBLE WITH ELECTRONIC AUXILIARY
No

NUMBER OF POSSIBLE ELEMENTS
1 element

COMPATIBLE WITH FLUORESCENT LAMPS WITH 1-10V DIMMABLE ELECTRONIC BALLAST
No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)
No

FREQUENCY
50 - 60 Hz

INDICATOR FUNCTION
Yes

IP RATING
IP20

COMPATIBLE WITH LOW CONSUMPTION (W)
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM QUANTITY PER CIRCUIT
2

TYPE OF MECHANISM
Detection

COMPATIBLE WITH MOTORS (VA)
No

OPERATING TEMPERATURE RANGE (°C)
0 - 35 °C

POWER SUPPLY (V~)
230 V~

APPROXIMATE RANGE (M)
6 m

TYPE
IR/Sound

VERSION
Single

NUMBER OF WIRES
2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
8

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
518400

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.195

PRODUCT NET WEIGHT
0.195

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053014165

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
81

PACKAGING WIDTH
80

PACKAGING LENGTH
80

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
518400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.195

PACKAGING NET WEIGHT
0.195

PACKAGING WEIGHT UNIT
KGM