

Flush-mount box for centres with 1 or 2 trunkings

REF. 05731-39



BASIC INFORMATION

DESCRIPTION

It measures 250x115 mm (width and height) and has a depth of 50 mm. The recessed box is used for 1- and 2-channel control panels and belongs to the wide and extensive range of products of the Simon 82 series. It is very comfortable and easy to install, as it is suitable to be recessed in the place where you want to place it. The material with which it has been manufactured is thermoplastic, capable of reaching temperatures ranging between 5 and 40°, and can support up to a maximum of -25° of minimum and 50° C maximum. The recessed box fulfils its function perfectly thanks to the guarantee and experience of a solid and specialized brand in the sector, if you have any questions do not hesitate to consult us, we will be pleased to assist you.

COMPATIBILITY

Simon 05 mechanisms

ETIM CLASS

EC002601

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INDICATOR FUNCTION

No

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Own

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.162

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

8112000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053059234

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.81

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

260

PACKAGING NET WEIGHT

0.81

UNITARY PACKAGING GROSS
WEIGHT

0.162

PACKAGING WIDTH

260

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

120