

## Complete kit with 2xUSB charger and 2 schuko socket outlets white S400 Top

REF. 42322000-130



### BASIC INFORMATION

#### DESCRIPTION

Simon offers a product designed for those workspaces that require all connections in one place. Within the 400 series, we find this complete surface kit with 2 x USB charger and 2 white schuko sockets. A cutting-edge product made of metal with a white finish, the decorative cover is made of painted steel with a very impact-resistant anodized aluminum profile. Simon provides extra safety in the unlikely event of combustion; its covers and fastenings prevent the flame from spreading as they are made of self-extinguishing thermoplastic. A product created for intensities of 16 amperes and a voltage of 250 volts.

#### FINISH

White

#### MATERIAL

Metal

#### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

#### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

#### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### IK CLASSIFICATION

07

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### OPERATING TEMPERATURE RANGE (°C)

-5...+60

### TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9016

### NUMBER OF SOCKETS

2 sockets for standard current circuit

### NUMBER OF USB CHARGERS

1

### VERSION

3 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### INSTALLATION TYPE

Suitable for fixing to furniture.

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053215968

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.71

### PRODUCT NET WEIGHT

0.71

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053215968

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

116

### PACKAGING LENGTH

213

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2223720

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.71

### PACKAGING WEIGHT UNIT

KGM