On-desk set with 5 German socket outlets aluminium Simon 400

REF. **42505000-133**



BASIC INFORMATION

DESCRIPTION

For the environment suits your needs, Simon 400 offers the kit full of 5 socket-outlets ground, ideal to optimise the space and to win in functionality in working areas. With aluminium finishes and a design of simple lines, the kit is integrated into all types of decorative spaces and environments. Its flush installation does not require additional tools, thanks to the quick connection Wieland, reducing the time of assembly and increasing the performance of the product, it also has a compact design of a dimension of 250 x 120 mm and a depth of 80 mm, making the installation and adapting the set in the space. Compatible with a voltage of power of 250 Volts, and 16 Ampere current, its resistance of insulation is > 5 M? at 500 V, with a dielectric strength of 2000 V at 50H per minute. This kit is the perfect solution to obtain a configuration versatile in a simple design and compact thanks to Simon 400.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9006

NUMBER OF SOCKETS
5 sockets for standard current circuit

VERSION
5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053195932

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.85

PRODUCT NET WEIGHT
0.85

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053195932

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
300

PACKAGING WIDTH
125

PACKAGING LENGTH
98

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3675000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.85

PACKAGING WEIGHT UNIT
KGM