

Floor trunking distribution baseboard with 3 punched holes and 1 pre-punched hole for DCS trunking stainless steel Simon Trunking

REF. KTA831/8



BASIC INFORMATION

DESCRIPTION

Floor trunking distribution baseboard with 3 punched holes and 1 pre-punched holes for DCS trunking made of stainless steel, which belongs to the series Simon Trunking. This product is made, taking into account all types of surfaces possible, therefore, has been created to be able to meet both to people with raised garden, and people with with concrete floors. It has been designed with 4 punched holes, allowing a very good distribution and branching of trunking, with which it manages to enable the integration of K45 mini columns on the socket baseboard from the adapter ALKA02 / 8. This product has dimensions of: 140 x 140 x 30 mm, and is made with a metallic finish that is brilliant and attractive. This type of finishes give to the decoration of a bonus, thanks to the light and modernity that provide to any type of space. To keep this piece in the best condition possible, always have to clean it with a soft and dry cloth, forgetting of use any type of a cloth and / or abrasive cleaner containing chlorine in its formulation, as this may damage it to be made of stainless steel.

FINISH

Metal

PACKAGING CONTENTS

Distribution plinth for floor trunking, protective foam, screws and installation manual

ETIM CLASS

EC002469

MATERIAL

Stainless steel

REMARKS

Designed with 4 pre-punched holes for DCS 85 x 18 mm trunking. See table in the event of requiring a different plinth configuration for the distribution of floor trunking. In addition to allowing the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the plinth base, using the adaptor ref. ALKA02/8

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam in the base of the distribution plinth.

AVAILABLE IN

1 to 3 punched holes 130 x 18 mm and 1 to 4 pre-punched holes 85 x 18 mm (see selection table)

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

HEAT RESISTANCE (°C)

+850°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

3 punched holes 130x18 mm DCS trunking and 1 pre-punched hole 85x18 mm DCS trunking

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Using supplied screws

INSTALLATION DIRECTION

Horizontal

INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436036611

PRODUCT NET WEIGHT

0.347

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1474200

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436036611

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.347

UNITARY PACKAGING VOLUME

1474200

PACKAGING HEIGHT

63

PACKAGING NET WEIGHT

0.347

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.347

PACKAGING LENGTH

156