

Kit Schuko Simon Scudo TOP IMPACT flush-mounted for electric vehicle charging IP44 IK09 16A ~3.7kW with lockable safety cover and screw terminal

REF. 0602004-039



BASIC INFORMATION

DESCRIPTION

The Simon Scudo TOP IMPACT Schuko Kit is a safe and durable solution for charging electric cars, motorcycles, or scooters at home. Designed for flush mounting, it offers up to 3.7 kW of power (16A, 250V) and is ready for extended charging in basic modes 1 and 2. Its IP44 protection rating and IK09 impact resistance guarantee durability in indoor spaces such as private garages and communal car parks. It features a hinged cover with a key that protects the connection point from unauthorised use, dust and moisture, and includes a customisable label strip that allows you to note the use or user assigned to the charging point, making it easy to identify in shared car parks. Compatible with Schuko-format portable chargers, it requires a dedicated line with a 2.5 mm² cable and an exclusive circuit breaker of up to 16 A, complying with current regulations for reliable and safe charging. The Simon Scudo TOP IMPACT Kit combines clean and careful aesthetics, safety and durability, making it an economical and safe alternative to conventional sockets that are not prepared for the energy demands of electric mobility.

FINISH

Aluminium

MATERIAL

Metal

SYMBOL

Label holder

ETIM CLASS

EC000125

REMARKS

One single plug per dedicated line with 2.5 mm² cross-section cables and with an exclusive circuit breaker up to a maximum of 16 A.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

MONOBLOCK

Yes

CONNECTOR TYPE

Schuko

CURRENT (A)

16 A

NOMINAL VOLTAGE (V~)

250 V~

DUST PROTECTION

Yes

INTERCOMMUNICATION FUNCTION

No

OPERATING TEMPERATURE RANGE (°C)

+5...+40

FORMAT

Schuko

IP RATING

IP44

RAL

9006

FREQUENCY

50 - 60 Hz

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

IK CLASSIFICATION

09

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053383261

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.47

PRODUCT NET WEIGHT

0.385

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053383261

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

113

PACKAGING WIDTH

125

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1836250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.47

PACKAGING NET WEIGHT

0.385

PACKAGING WEIGHT UNIT

KGM