

## Electronic switch/2-way switch module (ON/OFF) of up to 2300W

REF. 89000201-039



### BASIC INFORMATION

#### COMPATIBILITY

Any load (110V or 230V)

#### PACKAGING CONTENTS

Electronic circuit breaker/switch module and instructions

#### ETIM CLASS

EC001097

#### REMARKS

Can function as an independent switch for Scena because of its auxiliary input.

## TECHNICAL INFORMATION

### BASIC CHARACTERISTICS

Supplies an ON-OFF signal of up to 230V. Maximum power depending on the type of load, with push-button auxiliary input.

### PUSH BUTTON INPUT FOR CONTROL WITHOUT CONSOLE

Yes

### FREQUENCY (HZ)

50 - 60 Hz

### IP RATING

IP20

### MAXIMUM NUMBER OF CHANNELS

1

### MAXIMUM POWER INCANDESCENT AND HALOGENS AT 230 V (W)

2300 W

### TYPE OF MECHANISM

With Scena and/or auxiliary input in stand-alone mode

### OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

### OPERATION

On/Off

### POWER CABLE SECTION (MM)

1.5 mm

### POWER RANGE (KW)

0-2300 W

### POWER SUPPLY (V~)

127/230 V~

### STORAGE TEMPERATURE RANGE (°C)

0 - 45 °C

## INSTALLATION AND MAINTENANCE

### BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

### CABLE CHARACTERISTICS DATA

Multicore AWG 24; 2 shielded twisted pairs with impedance of 120 Ohms

### INSTALLATION DIRECTION

DIN rail

### INSTALLATION TYPE

DIN rail or false ceiling.

## REGULATIONS

### REGULATIONS

UNE-EN 50491-3:2010 + 2004/108/CE + 2006/95/CE

## LOGISTICS INFORMATION

UNITARY EAN CODE	UNITARY PACKAGING WEIGHT UNIT	UNITS CONTAINED PACKAGING
8421053096468	KGM	1
UNITARY PACKAGING GROSS WEIGHT	UNITARY PACKAGING WIDTH	PACKAGING MEASUREMENT UNIT
0.126	0	MMT
UNITARY PACKAGING HEIGHT	PACKAGING EAN	PACKAGING VOLUME
0	8421053096468	0.528
UNITARY PACKAGING LENGTH	PACKAGING GROSS WEIGHT	PACKAGING VOLUME UNIT
0	0	DMQ
PRODUCT NET WEIGHT	PACKAGING HEIGHT	PACKAGING WEIGHT UNIT
0.126	40	KGM
UNITARY PACKAGING VOLUME	PACKAGING LENGTH	PACKAGING WIDTH
0	120	110
	PACKAGING NET WEIGHT	
	0.126	