

MD-12 270° PIR+LUX BT Mesh wall surface On/Off white IP54

REF. 89202143-430



BASIC INFORMATION

DESCRIPTION

Wall-mounted PIR motion and light-level detector. Recommended installation height is 2 m, with a maximum height of 6 m. It has a detection angle of 270°. The tangential detection range is 12.5 m and the radial detection range is 2.7 m.

The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector is configured via a Bluetooth app. It has a TEACH operating mode. Sensors can be interconnected via Bluetooth.

The control output is On/Off and the maximum switching power is 2000 W.

Supply voltage is 220 - 240 VAC. Detector operating temperature: -20 - 40 °C.

White finish, IP 54 protection rating and dimensions: 87 x 82 x 98 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053462843

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.25

PRODUCT NET WEIGHT

0.17

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053462843

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

155

PACKAGING WIDTH

90

PACKAGING LENGTH

75

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1046250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.25

PACKAGING NET WEIGHT

0.17

PACKAGING WEIGHT UNIT

KGM