Customisable kit with 2xUSB charger, 4 schuko socket outlets and 1 empty element black S400 Top

REF. **42624000-138**



BASIC INFORMATION

DESCRIPTION

Did you know that you can have all the necessary connections fixed on the furniture? The Simon 400 Top series offers you this possibility thanks to this customizable table kit with a charger for 2 USBs, 4 schuko sockets, and an empty space for customization. A perfect product for workspaces, thanks to its manual lifting system, we can connect comfortably and hide it when necessary. Made of metal and with an excellent finish in black, it features a painted steel trim cover and an anodized aluminum profile that provides great strength and durability to the product. The 400 series is designed to prevent fires since both its covers and supports are made of self-extinguishing thermoplastic, which means they would prevent the spread of flames in case of an accident. 6 element kit designed for a current of 16 amperes and a voltage of 250 volts, its dimensions are 295 x 120 x 80 millimeters.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

NUMBER OF POSSIBLE ELEMENTS
1

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

NUMBER OF REAR ENTRANCES
1

NUMBER OF SOCKETS
4 sockets for standard current circuit

NUMBER OF USB CHARGERS
1

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

REMOVAL OF THE PLATE
Only with tool

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053273562

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
1.09

PRODUCT NET WEIGHT
1.09

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053273562

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
90

PACKAGING WIDTH
116

PACKAGING LENGTH
303

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3163320

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.09

PACKAGING WEIGHT UNIT
KGM