

Downlight 705.23 Directional NW Wide Flood 1-10V Aluminium

REF. 70523133-484



BASIC INFORMATION

DESCRIPTION

If you are looking for a uniform lighting, sustainable and long duration, the downlight 705.23 of the collection Simon guarantees a comfortable lighting and with the latest LED technology. Its light provides the space a white tone of a neutral (NW), due to its colour temperature of 3900 K, fully sustainable for the environment by their category A. With WIDE FLOOD optics for amplitude angle more, it is perfect for lighting in corridors, transit areas, or for general lighting of offices, commercial spaces, etc., and also includes 1-10V protocol of adjustment of the light flux light, adapting it to every need specific. With a performance of 1080 lm for NW, and a power consumption of the luminaire of 15.5 W, has a power of 100-240 Volts and 50-60 Hz and a service life of 30,000 hours at an average temperature of 25 °C. Designed for flush installation, suitable for false ceiling and / or plastered, is finished in Aluminium, which provide an industrial minimalist appearance that integrates seamlessly into all types of spaces.

APPLICATION

Ambient lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

1080 lm/15,5W

IP RATING

IP20

ELECTRICAL CLASS

Type 2

OPTICS

Wide Flood

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

POWER (W)

15.5 W

COLOR TEMPERATURE (K)

3900 K

COLOR TYPE

NW

POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

70 lm/W

SERVICE LIFE

30.000 h


CRI

80

LUMENS (LM)

1080 lm

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

136

INSTALLATION TYPE

Flush mount

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053122327	3.034
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	135	0.502
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.502	145	0.502
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.502	155	KGM