

Angled voice and data plate with dust cover for 1 element with 1 RJ45 category 6A FTP graphite Simon 500 Cima

REF. 50001081-038



BASIC INFORMATION

DESCRIPTION

In graphite finishes, the plate of voice and data tilted plate with dust cover with 1 element with RJ45 category 6A FTP is part of the Simon 500 Cima series and offers dimensions of 50x50x54. Its manufacture with metal components with self-extinguishing, halogen-free thermoplastic insulation, guarantees no flame propagation if any fire and low toxicity in case of smoke. The plate includes clips for fastening in vertical and horizontal enclosures without the need of adapter, although both it as RJ45 connectors. All this indicates that the collection Simon 500 Cima brings together the safest solutions for the most demanding market for our customers. So that forget of all and confident in our specialists to make your home in the site safer.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with dust cover, RJ45 connector category 6A FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

80

UNITARY PACKAGING WIDTH

224

UNITARY PACKAGING LENGTH

290

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

5196800

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.059

PRODUCT NET WEIGHT

0.059

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053097717

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

80

PACKAGING WIDTH

224

PACKAGING LENGTH

290

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.052

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.18

PACKAGING WEIGHT UNIT

KGM

