

## Luminaire A20 BT Mesh 12,4W 4000K with detector 8m HF+LUX anthracite IP54 IK10

REF. 89391602-124



### BASIC INFORMATION

#### DESCRIPTION

Luminaire with integrated HF detector and Bluetooth connectivity. The power is 12.4 W, the luminous flux is 1427 lm, and the color temperature is 4000 K.

The maximum installation height is 4m, and the installation is surface-mounted. The detection range is 8m, and the detection angle is 360°.

The brightness regulation range is 2 - 2000 lux, and the timing range is 10 s - 60 min.

The luminaire configuration is done through a Bluetooth application. Possibility of interconnection between luminaires via Bluetooth mesh.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C.

Protection degree IP 54 and IK 10, and dimensions: Ø 262 x 69 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

#### FINISH

Anthracite

#### ETIM CLASS

EC002892

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### IP RATING

IP54

### IK CLASSIFICATION

10

### POWER SUPPLY (V~)

220/240 V~

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053383438

### UNITARY PACKAGING GROSS WEIGHT

0.99

### PACKAGING LENGTH

85

### UNITARY PACKAGING HEIGHT

0

### PRODUCT NET WEIGHT

0.99

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

2325323

### UNITARY PACKAGING LENGTH

0

### PACKAGING EAN

8421053383438

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITS CONTAINED PACKAGING

1

### PACKAGING GROSS WEIGHT

0.99

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

310

### PACKAGING NET WEIGHT

0.99

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING WIDTH

310

### PACKAGING WEIGHT UNIT

KGM