

Modular Luminaire Simon 730 120x10 3000 K General 1-10 V Emergency Kit

REF. 73062840-883



BASIC INFORMATION

DESCRIPTION

Simon creates the 730 series, an innovative and technical indoor luminaire ideal for installation in functional environments with false ceilings. With a general optics and a dimming on control of 1-10 V. Includes a kit for emergency situations where there is a tension fall.

It emits 3400 lm and has power consumption of 34.5 W with a service life of 100,000 h at 25°C for the L70. It has IP 44 protection and its optics offers a light beam aperture angle of 100 degrees.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

3400 lm/ 34,5W

IP RATING

IP44

L70 (°C)

100.000 h at 25°C

OPTICS

General

OPERATING TEMPERATURE RANGE (°C)

0 to 40° C

L90 (°C)

50.000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

POWER SUPPLY (V~)

230 V~

LIGHT BEAM APERTURE ANGLE (°)

100°

POWER (W)

34,5 W

COLOR TEMPERATURE (K)

3000K

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

99 lm/W

DIRECTIONAL

No

LUMENS (LM)

3400 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted | Concealed ceiling | Semi-concealed ceiling | Flush-mounted

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053204627

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0

PRODUCT NET WEIGHT

0.28

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053204627

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

87

PACKAGING WIDTH

110

PACKAGING LENGTH

1215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

11627550

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.31

PACKAGING NET WEIGHT

0.28

PACKAGING WEIGHT UNIT

KGM