

Socket 16A 250V ~ with connection system 1click® Simon 100

REF. 10000458-039



BASIC INFORMATION

COMPATIBILITY

Frames Simon 100

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

CURRENT (A)

16 A

OPERATING TEMPERATURE

RANGE (°C)

0 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 75 °C

FORMAT

French

TYPE OF MECHANISM

Insertion

VERSION

Unique

MONOBLOCK

No

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

universal

INSTALLATION TYPE

Suitable for flush mounting

CLAW

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

1 click connection (1 click®)

REGULATIONS

REGULATIONS

EN 50581:2012 + IEC 60884-1 Ed 3.2

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053142097

PACKAGING VOLUME
1584375

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
65

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.045

PACKAGING WIDTH
125

PACKAGING NET WEIGHT
0.46

PRODUCT NET WEIGHT
0.046

PACKAGING LENGTH
195

PACKAGING WEIGHT UNIT
KGM

