Complete kit with 2xUSB charger and 2 schuko socket outlets black S400 Top

REF. **42322000-138**



BASIC INFORMATION

DESCRIPTION

Simon offers a product designed for those workspaces that require all connections in one place. Within the 400 series, we find this complete desktop kit with a 2 x USB charger and 2 schuko sockets in black. A cutting-edge product made of metal with a black finish, the trim cover is made of painted steel with a profile of anodized aluminum that is very resistant to impacts. Simon provides extra safety in the unlikely event of combustion; its covers and fastenings prevent the flame from spreading as they are made of self-extinguishing thermoplastic. A product created for 16 amp intensities and a voltage of 250 volts.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

IK CLASSIFICATION
07

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
-5...+60

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

NUMBER OF SOCKETS
2 sockets for standard current circuit

NUMBER OF USB CHARGERS
1

VERSION
3 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053215982

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.64

PRODUCT NET WEIGHT
0.64

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053215982

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
90

PACKAGING WIDTH
116

PACKAGING LENGTH
213

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2223720

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.64

PACKAGING WEIGHT UNIT
KGM