
Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 6 FTP aluminium Simon K45

REF. **KA96F/8**



BASIC INFORMATION

DESCRIPTION

Model of plate for KA96F / 8 Voice and data connections, forming part of the range of Simon components K compatible With the use of other elements and components of the same range. It is a plate of voice and Data version plate with dust cover with 1 element for 1 RJ45 connector of Category 6 FTP with snap-fit Keystone I, II, ATT ® / Avaya ® with insertion tool. Number of modules quarter full with colour and finishes In graphite. It is compatible with element 90º positioner (ref. K66) to guide the plate into a vertical position. Composed Metal components with self-extinguishing thermoplastic insulation And halogen-free; guarantees no flame propagation in case of Fire and the low toxicity, ensuring maximum security professionally. It measures 45x45mm and 42,9mm, ideal to adapt to any kind of systems and installations in Different environments.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 6 FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+60º C

DUST PROTECTION
Yes

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-5 to 60º C

NUMBER OF MODULES
Four

PLATE TYPE
Flat

RJ45 ADAPTOR MODULE
Supplied with the voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.032

PRODUCT NET WEIGHT
0.032

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436046214

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.32

PACKAGING NET WEIGHT
0.16

PACKAGING WEIGHT UNIT
KGM