Satellite socket single F type female with trim plate white Simon K45

REF. **K102C/9**



BASIC INFORMATION

DESCRIPTION

Simon is without doubt synonymous with quality, innovation, appearance and security. For over 100 years have achieved provide us the best products for inside and outside of the home and be able to get the most complete work stations and business environments, always, without losing a pinch in elegance, thanks to its modern and avant-garde designs. Within the workplace solutions for the home, we find the collection K45, focused on improving any type of connection where it is needed. This is why this range is designed for offices, meeting rooms, hospitals or any public space. In this series, K45, we find this single satellite socket, female, with trim. Of a module and half element, this single F type have a finish is white in colour and can be applied to both to be recessed and surface-mounted. Supports a maximum length of 90 metres wire RG-6 and dimensions 22.5 x 45 mm

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Simple F type female satellite socket

ETIM CLASS

EC000439

REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 6 to 8 mm

CONNECTOR TYPE
SAT

NUMBER OF CONTACTS
1

NUMBER OF POSSIBLE ELEMENTS
1/2 element

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
9003

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
1

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 50083-2:2012 + A1:2015 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
91140

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.014

PRODUCT NET WEIGHT
0.014

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436046528

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.14

PACKAGING NET WEIGHT
0.14

PACKAGING WEIGHT UNIT
KGM