

Charger 5V DC via USB port type A and micro USB patch cord with cable winder graphite Simon K45

REF. K126A/14



BASIC INFORMATION

DESCRIPTION

Since SV / DC charger through type A USB port and micro-USB patch cord, with cable-winder. It has a stylish finished in graphite colour and belongs to the series Simon K45. This charger has a current of 1.5 A and a power of 230 V. its clamping is by screw. It is of individual version, of two modules, which lawyer by the operation is by insertion. It is important to take into account that allows simultaneous charging of two devices, one connected through the type A USB connector and the other through the micro USB patch cord. The dimensions of this charger specific Simon are 45 x 45 millimetres, with a depth of 43 millimetres. Supports a wire section of between 1 and 2.5 millimetres and requires a stripped wire 6 millimetres. It is manufactured from metal components, isolated with self-extinguishing thermoplastic and halogen-free. Thanks to this it can withstand extreme temperatures, ranging from -25 to the + 50 degrees centigrade. It can be installed both on the surface-mounted and flush mounted and its maintenance only requires a simple, clean using a soft and completely dry cloth.

FINISH

Graphite

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

USB charger, trim cover with cable-winder, micro USB patch cord and installation manual

REMARKS

Allows simultaneous charging of a device connected through the type A USB connector and a device connected through the micro USB patch cord

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

1,5 A

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

From 1,0 to 2,5 mm

IP RATING

IP20

NUMBER OF MODULES

2 modules

NUMBER OF CONNECTIONS PER TERMINAL

1 connection per terminal

KIT AVAILABILITY

Yes

MONOBLOCK

No

MAX TEMP DURING CONSTRUCTION WORK (°C)

0 a 45° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

FORMAT

USB / Micro-USB

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 50° C

VERSION

Single

VOLTAGE (V~)

230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

6

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE SOCKET

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-038

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

2 inputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2013 + ETSI-EN 301489-34 V1.4.1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053092507

PACKAGING VOLUME

0.329

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

57

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.086

PACKAGING WIDTH

76

PACKAGING NET WEIGHT

0.086

PRODUCT NET WEIGHT

0.086

PACKAGING LENGTH

76

PACKAGING WEIGHT UNIT

KGM