Projector 889 50W 3000K

REF. **88932038-883**



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for lighting of shop windows and facades, robust, adjustable, and designed for high performance in commercial applications. Available in different power ratings, the Outdoor Projector 889 allows you to select the appropriate model according to the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 3000K. Power: 50W. Lumens: 5550lm. Efficiency: 111lm/w. Protection degree IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 185 mm x 162 mm x 35 mm.

APPLICATION

Wall lighting,Industrial lighting,Commercial areas

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
05

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+50

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
111 lm/W

LUMENS (LM)
5550 lm

OPTICS
Symmetric

POWER (W)
50 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440308

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.519

PRODUCT NET WEIGHT
0.48

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440308

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
195

PACKAGING WIDTH
220

PACKAGING LENGTH
400

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
17160000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
5.19

PACKAGING NET WEIGHT
0.48

PACKAGING WEIGHT UNIT
KGM