

## IP66 Mechanism holder and security frame with schuko and RJ45 5e UTP

REF. KFH115USEC/74



## BASIC INFORMATION

### DESCRIPTION

Simon completely renews its range of waterproof floor boxes for indoor and outdoor environments. This is a device frame with a security lock for environments that require restricted access, featuring a Schuko socket and a category 5e UTP RJ45 connector. In combination with its base, it allows installation in technical flooring or pavement. The product design, combined with its stainless steel construction, achieves a robust, solid, and secure installation as it can withstand a water jet of 1 kg/cm<sup>2</sup> from any direction, achieving an IP66 protection rating when the cover is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal bending radius for high-category voice and data connections. Our accessory for connecting a plug with a closed cover is available, allowing us to keep our connections active with an IP54 (see reference KFA1001), the possibility to level our box in case of irregular flooring (see reference KFA1003), or the capability to cascade more than one box (see reference KFA1002).

### FINISH

Black

### COMPATIBILITY

K45 Solutions

### MATERIAL

Polycarbonate

### ETIM CLASS

EC000024

### REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

## TECHNICAL INFORMATION

### FORMAT

Schuko

### IP RATING

IP66

### MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

### IK CLASSIFICATION

08

### KIT AVAILABILITY

Yes

### VOLTAGE (V~)

250 V~

### CURRENT (A)

16 A

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

### REMOVAL OF THE SOCKET

Only with tool

### NUMBER OF COVER OPENING POSITIONS

1

### REMOVAL OF THE FRAME

Only with tool

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 50173-1:2018 | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 |

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053332795

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053332795

PACKAGING VOLUME

1837680

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

114

PACKAGING GROSS WEIGHT

0.157

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

124

PACKAGING NET WEIGHT

0.13

UNITARY PACKAGING GROSS  
WEIGHT

0.157

PACKAGING LENGTH

130

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.13