

Canal pasacables PVC de 2m y 160x55mm para 4 separaciones

REF. TS16055/9



BASIC INFORMATION

DESCRIPTION

Our PVC cable guide trunking of 2 meters is a durable and efficient solution for cable management in electrical projects. Made with high-quality PVC, it meets safety standards by being flame-retardant in case of fire. With specialized internal design dimensions, it facilitates effective cable organization. With IP4X and IK07 certification, we guarantee an exceptional level of protection for your electrical installations. We offer a versatile range of accessories to adapt it to different architectural configurations, as well as the possibility to incorporate universal Simon mechanisms using the corresponding adapters. The indicated price is per meter and is supplied in batches of 6 units (12 meters in total)

FINISH

White

MATERIAL

PVC

ETIM CLASS

EC001938

TECHNICAL INFORMATION

IK CLASSIFICATION

07

KIT AVAILABILITY

No

RAL

9003

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436048690

PACKAGING VOLUME

82976124

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

12

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

2018

PACKAGING GROSS WEIGHT

28.5

UNITARY PACKAGING GROSS WEIGHT

2.375

PACKAGING WIDTH

178

PACKAGING NET WEIGHT

28.5

PRODUCT NET WEIGHT

2.375

PACKAGING LENGTH

231

PACKAGING WEIGHT UNIT

KGM