

Neutral push-button switch 10AX 250V~ with housing for
pictogram and fast terminal connection system ivory
Simon 31

REF. 31659-31



BASIC INFORMATION

DESCRIPTION

Neutral push-button switch, series Simon 31, in ivory colour and with housing for pictogram system and quick terminal connection. Its current is 10 A and its voltage of 250V. It also has a tilting type operation. This push-button switch is available in 3 finishes and is always recommended to choose the frame in the same colour as the rocker selected. 1 element and 2 modules and supports a wire cross section of 1.5 to 2.5 mm, with a stripping of 11 mm. It can be installed in rooms with a temperature of between 5 and 40°C, although it can withstand extreme temperatures of -25 to 50°C, approximately, making it ideal for all types of climates. Complies with the regulations UNE -s 60669-1: 2002 + A1: 2003 + A2: 2009 and is manufactured with metal components with halogen-free insulation and thermoplastic trim metal, a material very easy to clean, as you just wipe it with a soft cloth slightly moistened in soapy water, without resorting to cloths or abrasive cleaners with chlorine.

FINISH

Ivory

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

REMARKS

Available in 3 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053007396

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

83

PACKAGING GROSS WEIGHT

0.76

UNITARY PACKAGING GROSS WEIGHT

0.076

PACKAGING WIDTH

165

PACKAGING NET WEIGHT

0.76

PRODUCT NET WEIGHT

0.076

PACKAGING LENGTH

221

PACKAGING WEIGHT UNIT

KGM