

Voice and data angled plate with dust cover for 1 element and 2 RJ45 connectors category 6 UTP white Simon K45

REF. KB8096U/9



BASIC INFORMATION

DESCRIPTION

This is one of the angled voice and data plates of the series Simon K45 commitment to a discreet and versatile finished in white colour. Includes a dust shutter and is an element and 2 RJ45 category 6 UTP. This is, specifically, the individual version half module. The plate has the exact dimensions of 45 x 45 millimetres and 46,6 millimetres of depth. It can be installed both in the wall and on a surface-mounted. Commitment to the highest quality and security, thanks to its manufacturing materials, which is based on metal components, isolated thermoplastically and halogen-free. This makes it possible to withstand maximum temperatures of up to + 60 degrees centigrade. For the installation of this plate Simon in vertical enclosures, it is necessary to use the 90 ° positioner of the brand reference (: K66). Its connection is made from the insertion tool.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Voice and data tilted plate with dust cover, direct modules for snap-fit connector and category 6 RJ45 UTP connectors

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with voice and data plate

CONNECTOR CHARACTERISTICS

Category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

NUMBER OF MODULES

Half

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.04

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436040335

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

287138

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.35

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.4

UNITARY PACKAGING GROSS WEIGHT

0.04

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195