Module Downlight LED Simon 704 4000K Spot Negro

REF. **70400038-284**



BASIC INFORMATION

APPLICATION

Accent lighting,General lighting

ETIM CLASS

EC000996

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
-15 to 35ºC

POWER SUPPLY (V~)
220/240 V~

COLOR TEMPERATURE (K)
4000K

CONTROL
On/Off

CRI
80

LIGHT BEAM APERTURE ANGLE (°)
20º

LIGHTING EFFICIENCY (LM/W)
91 lm/W

LUMENS (LM)
1101 lm

LUMENS/W
1101 lm/12W

OPTICS
Spot

SERVICE LIFE
30.000 h

CHROMATICS CRI ICONS



REGULATIONS

WARRANTY
3 years 30.000 h

REGULATIONS
Dir. 2014/30/UE EMC | Dir. 2014/35/UE LVD | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 55015:2019 + A11:2020 | EN IEC 60598-2-1:2021 | EN IEC 61547:2023 | EN 60598-2-2:2012 | EN 61000-3-3:2013 + A1:2019 + A2:2021 | EN 62493:2015 | EN IEC 63000:2018 | EN 62717:2017 + A2:2019

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053225493

UNITARY PACKAGING HEIGHT
115

UNITARY PACKAGING WIDTH
85

UNITARY PACKAGING LENGTH
118

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
1.153

UNITARY PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING GROSS WEIGHT
0.274

PRODUCT NET WEIGHT
0.23

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053225493

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
115

PACKAGING WIDTH
85

PACKAGING LENGTH
118

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1153450

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.274

PACKAGING NET WEIGHT
0.23

PACKAGING WEIGHT UNIT
KGM