

## Frame and frame holder for surface mount and flush mount wall box for 1 element black Simon K45

REF. KR245/14



### BASIC INFORMATION

#### FINISH

Black

#### COMPATIBILITY

Simon K45 functions

#### ETIM CLASS

EC000007

#### MATERIAL

Plastic

#### PACKAGING CONTENTS

Wall frame for surface-mounted or flush-mounted box and frame holder

#### REMARKS

The article includes frame holder with housing for fitting onto a universal flush-mount box

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

### NUMBER OF MODULES

1 wide module

### AVAILABLE IN

1 and 2 elements

### IP RATING

IP4X

### RAL

7021

### DIELECTRIC STRENGTH

Without perforation or  
contournement with 2000 V at  
50H during 1 minute

### KIT AVAILABILITY

No

### RECESS DIMENSION (MM)

75 x 70 mm

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

### MAINTENANCE

Clean with a soft, dry cloth. Do  
not use abrasive cloths or  
cleaning products that contain  
chlorine.

### VERSION

1 element

### HEAT RESISTANCE (°C)

+70°C (in accordance with IEC  
60670-1:2006)

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for installing flush-  
mounted into wall or on the  
base of the surface-mounted  
wall box

### EXTINGUISHING (°C)

+650 °C / 30 seconds (GWFI  
according rule IEC 60695-2-11)

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

### TYPE OF FASTENING

Through direct snap-fit on to  
frame holder supplied (does not  
require the use of tools for  
fastening)

### INSTALLATION DIRECTION

Horizontal, Vertical

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### PRODUCT NET WEIGHT

0.029

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

3325000

### UNITARY PACKAGING LENGTH

0

### PACKAGING EAN

8426436050655

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING VOLUME

60361

### UNITS CONTAINED PACKAGING

20

### PACKAGING GROSS WEIGHT

0.62

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING HEIGHT

100

### PACKAGING NET WEIGHT

0.58

### UNITARY PACKAGING GROSS WEIGHT

0.029

### PACKAGING WIDTH

190

### PACKAGING WEIGHT UNIT

KGM

### PACKAGING LENGTH

175