

## Downlight 725.27 4000K DALI

REF. 72527330-884



### BASIC INFORMATION

#### APPLICATION

General lighting

#### PACKAGING CONTENTS

1 unit

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### LUMENS/W

1525 lm/14W

### IP RATING

IP44

### ELECTRICAL CLASS

Type 2

### OPTICS

General

### OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

### L70 (°C)

54.000 h at 25°C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### POWER SUPPLY (V~)

220/240 V~

### LIGHT BEAM APERTURE ANGLE (°)

115°

### POWER (W)

14 W

### COLOR TEMPERATURE (K)

4000 K

### LIGHTING EFFICIENCY (LM/W)

108 lm/W

### SERVICE LIFE

50.000 h

### CONTROL

DALI

### LUMENS (LM)

1525 lm

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Flush mount

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053282465

### UNITARY PACKAGING HEIGHT

55

### UNITARY PACKAGING WIDTH

18

### UNITARY PACKAGING LENGTH

22

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

21780

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.56

### PRODUCT NET WEIGHT

0.328

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053282465

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

55

### PACKAGING WIDTH

18

### PACKAGING LENGTH

22

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

21780

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.56

### PACKAGING NET WEIGHT

0.328

### PACKAGING WEIGHT UNIT

KGM