Hinged cover for adjustable floor box or service cover in concrete or raised floor for 2 elements graphite Simon 500 Cima

REF. **RSF001/14**



BASIC INFORMATION

DESCRIPTION

Hinged cover for adjustable floor box or service cover of the Simon 500 Cima series graphite in colour and has 2 elements, this cover is perfect for re-usage purposes embedded in concrete or recessed in raised floor. For its installation, which can be done in concrete floor or raised floor, you through the adjustable floor boxes or inspection covers. This cover has been made in the regulation UNE-EN 60.670-23 plastic graphite in colour and, in addition, it has metallic components with self-extinguishing, halogen-free thermoplastic insulation, which means that it is a material very safe as that guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation. It measures 105 x 161 x 15 mm and for cleaning, just, it is necessary to use a soft and dry cloth.

FINISH

Graphite

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

AVAILABLE IN
2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+90 °C

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
>5 MOhms at 500V

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

NUMBER OF MODULES
2 modules

RAL
7021

VERSION
2 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING
Via coupling pin supplied on the cover

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS
UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436056176

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.346

PRODUCT NET WEIGHT
0.346

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436056176

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
20

PACKAGING WIDTH
220

PACKAGING LENGTH
150

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.66

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.346

PACKAGING WEIGHT UNIT
KGM