

LedFlex 810.34 3000 K IP20 HE

REF. 81034000-983



BASIC INFORMATION

APPLICATION

General lighting, Indoor
decorative lighting

PACKAGING CONTENTS

1 unit (5m)

ETIM CLASS

EC002706

TECHNICAL INFORMATION

IP RATING

IP20

DRIVER INCLUDED

No

LUMENS (LM)

4800 lm

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

LUMENS/W

4800 lm/36W

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

PWM

COLOR TYPE

WW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

133,3 lm/W

POWER (W)

36 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053202593

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053202593

PACKAGING VOLUME

1200

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

2

PACKAGING GROSS WEIGHT

0.29

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

24

PACKAGING NET WEIGHT

0.171

UNITARY PACKAGING GROSS
WEIGHT

0.29

PACKAGING LENGTH

25

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.171