

Flat voice and data plate without dust cover for 1 element with 1 RJ45 category 6A FTP white Simon 500 Cima

REF. 50001185-030



BASIC INFORMATION

DESCRIPTION

Flat base plate of voice and data, of the Simon 500 Cima series. Includes a dust shutter and has an element for an RJ45 connector. The category to which is part of the plate is 6A FTP and its finish is fully white. This provides functionality to the product, as it is easy to integrate into any space. The individual version of the voice and data plate has a module and includes the clips necessary to place it in horizontal or vertical enclosures. It is not necessary to take the specific tools for its adaptation. Its exact dimensions are 50 x 50 x 44 millimetres. This makes it quite compact. This plate of the Simon 500 Cima series has been designed from metal materials thermoplastically isolated and free of halogens. In this way is achieved to increase the security of the plate for its use. Also, in the event of smoke, the toxicity is minimal. The maintenance of the Simon 500 Cima series is very simple, since it is enough to use a soft cotton for cleaning.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate without dust cover, category 6A FTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053098110

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.06

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.2

PRODUCT NET WEIGHT

0.06

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

