

Customisable kit with cover and brush, 1 schuko socket outlet and 4 empty elements black S400 Indesk

REF. 44501000-138



BASIC INFORMATION

DESCRIPTION

Kit, black in colour finish, belonging to the series Simon 400 Indesk and with cover, brush strip, 1 ground and 4 empty elements. Its dimensions are 295 x 185 x 85 mm and has a current of 16 A and works with a voltage of 250V. It can be installed flush-mounted in furniture and for its need to use the fastening claws that incorporates this kit or screws (in the holes available). Also, to complete the installation of the product, you will need to combine the kit with the Simon 400 Indesk (references 4000XXX-03X). Its enclosure is manufactured in painted steel, the profile in anodised aluminium and the covers and fastenings in self-extinguishing halogen-free and thermoplastic, a material very safe that promotes the no flame spread in case of fire and low toxicity. When cleaning, just wipe it with a soft and dry cloth, forgetting to use any cloth or abrasive cleaner containing chlorine.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

NUMBER OF POSSIBLE ELEMENTS

4

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

NUMBER OF REAR ENTRANCES

4

RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

NUMBER OF SOCKETS

1 socket for standard current circuit

VERSION

5 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196380

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.9

PRODUCT NET WEIGHT

1.9

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196380

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

320

PACKAGING WIDTH

195

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5928000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.9

PACKAGING WEIGHT UNIT

KGM