2-way rotary dimmer switch 40 to 500 W/VA white Simon 32

REF. **32813-35**



BASIC INFORMATION

DESCRIPTION

Control the light intensity of each room with the regulator 2-way switch rotary - of the collection Simon 32. With finishes in white and a simple design and modern, this mechanism Simon adapts to all kinds of decorative spaces and environments, adding maximum functionality and innovation. It is compatible with power supplies with a voltage of 230 Volts, supports an interval of intensity from 40 to 500 W / VA. It also supports a wire cross section of 1.5 to 2.5 mm and stripping of 5 mm The regulator 2-way switch Simon 32 -, you can reach a temperature range from 0 to 40 ° C and a maximum of -20 to the 75 ºC. It has an installation with screw terminal connection that guarantees the integration of the set in the space, making its adapting to all types of ambientes.Sin, in the same circuit cannot be connected two electronic voltage regulators.

FINISH

White

COMPATIBILITY

Simon 32 frames with circular central opening

COMPATIBLE WITH MECHANICAL 2-WAY/CROSSOVER SWITCH

Yes

COMPATIBLE WITH 230V INCANDESCENT AND HALOGEN LAMPS (W)

500 W/VA

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

COMPATIBLE WITH MECHANICAL SWITCH

No

PACKAGING CONTENTS

Dimmer and instruction sheet

REMARKS

Two main electronic voltage regulators cannot be connected in the same circuit.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

NUMBER OF CONTACTS
3

NUMBER OF CONTROLLABLE CIRCUITS
1

COMPATIBLE WITH HALOGENS WITH ELECTROMAGNETIC TRANSFORMER (W)
350 W

COMPATIBLE WITH ELECTRONIC AUXILIARY
No

NUMBER OF POSSIBLE ELEMENTS
1 element

COMPATIBLE WITH FLUORESCENT LAMPS WITH 1-10V DIMMABLE ELECTRONIC BALLAST
No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)
No

INDICATOR FUNCTION
No

IP RATING
IP20

COMPATIBLE WITH LOW CONSUMPTION (W)
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM POWER (W)
500

MAXIMUM QUANTITY PER CIRCUIT
1

TYPE OF MECHANISM
Rotary

MINIMUM POWER (W)
40

COMPATIBLE WITH MOTORS (VA)
No

OPERATING TEMPERATURE RANGE (°C)
0 - 40 °C

POWER SUPPLY (V~)
230 V~

VERSION
Single

NUMBER OF WIRES
2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
5

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal and American

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2014/30/UE EMC|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-2-1:2004|EN 60669-2-1:2004 A1:2009|EN 60669-2-1:2004 A12:2010|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
329232

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.16

PRODUCT NET WEIGHT
0.16

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053012949

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
57

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
329232

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.16

PACKAGING NET WEIGHT
0.16

PACKAGING WEIGHT UNIT
KGM