

Projector 889 50W 4000K

REF. 88932038-884



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for shop window and facade lighting, robust, adjustable, and designed for high performance in commercial applications. Available in various power ratings, the outdoor projector 889 allows the selection of the appropriate model based on mounting height, surface to be illuminated, and desired impact level. Installation type: Surface. Optics: 110. Color temperature: 4000K. Power: 50W. Lumens: 4500lm. Efficiency: 90lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 185 mm x 162 mm x 35 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

90 lm/W

LUMENS (LM)

4500 lm

OPTICS

Symmetric

POWER (W)

50 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440353

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.519

PRODUCT NET WEIGHT

0.48

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440353

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

195

PACKAGING WIDTH

220

PACKAGING LENGTH

400

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

17160000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

5.19

PACKAGING NET WEIGHT

0.48

PACKAGING WEIGHT UNIT

KGM