

Adjustable depth trap for 6 modules S to be installed in concrete graphite color Simon CIMA

REF. SF670/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With Simon Series S and Simon 25 / Simon K45 (via adapter) mechanisms

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

16

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1800kg

RAL

7021

RECESS DIMENSION (MM)

210 x 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica y metálica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052772

PRODUCT NET WEIGHT

2.292

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

7483280

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436052772

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.292

UNITARY PACKAGING VOLUME

7483280

PACKAGING HEIGHT

79

PACKAGING NET WEIGHT

2.292

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

236

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2.292

PACKAGING LENGTH

342