

**French double socket outlet 16A 250V~ with safety device
and screw terminal connection pin unlocking red Simon
500 Cima**

REF. 50000459-037



BASIC INFORMATION

DESCRIPTION

With unlocking pin included, the French socket-outlet Simon 500 Cima double, provides the perfect balance between design, functionality and security adapted to any type of space. With finishes in a intense and original red tone, this socket-outlet has a design of neutral lines, ideal for working areas. With safety device included, it has a size of 100 x 50 mm and a depth of 46 mm Compatible with a power of 250 Volt voltage and 16 Ampere current, its installation is suitable for flush mounted or surface-mounted, with screw terminal connection, to ensure the integration of the set in all types of spaces. To protect your room in case of fire, it is made of metal materials isolated with self-extinguishing halogen-free thermoplastic that prevents flame spread and toxicity by smoke. Also, it can reach maximum temperatures of more than 60 °C.

FINISH

Red

PACKAGING CONTENTS

Double socket outlet with cover
and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The article includes the pins for unlocking the security shutters

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

AVAILABLE IN

German and French format

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

FORMAT

French

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

No

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

No

LINKABLE

Yes, using accessory 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 60 °C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2

MONOBLOCK

No

RAL

3002

NUMBER OF SOCKETS

2

VERSION

Double

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	PRODUCT NET WEIGHT	PACKAGING WIDTH
0	0.3	0
UNITARY PACKAGING WIDTH	UNITARY PACKAGING WEIGHT UNIT	PACKAGING LENGTH
0	KGM	0
UNITARY PACKAGING LENGTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053106389	0
UNITARY PACKAGING VOLUME	UNITS CONTAINED PACKAGING	PACKAGING GROSS WEIGHT
0	10	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING HEIGHT	PACKAGING NET WEIGHT
0.3	0	3
		PACKAGING WEIGHT UNIT
		KGM

