

Flat voice and data plate without dust cover for 1 RJ45 3M® for 1 element graphite Simon 500 Cima

REF. 50011185-038



BASIC INFORMATION

DESCRIPTION

In graphite finishes, the flat base plate of voice and data is available without dust cover and 1 element for 1 3M ® RJ45 that is part of the Simon 500 Cima series. Its measures are 50x50x11 mm, a thickness of 11 mmm and has been used components halogen-free in its manufacture. In this way, it guarantees no flame propagation in case of fire and a minimum toxicity in case of smoke. Finally, the plate includes clips for fastening in vertical and horizontal enclosures without the need of adapter. Is the most advanced solutions for your home thanks to our Simon 500 Cima series, one of the safest of our signature thanks to the use of the best materials of the market. So that you the games and confident in our brand to make your home the best place for live.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

No

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Volition OCK®, RJ25, K5e and K6 from 3M®.

IP RATING

IP20

RAL

7021

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

RJ45 3M® connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

SNAP-FIT TYPE

RJ45 3M® connectors

DUST PROTECTION

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053096697

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0.14

UNITARY PACKAGING GROSS WEIGHT

0.014

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.14

PRODUCT NET WEIGHT

0.014

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

