


Mechanism-holder unit IP66 with manual lock and Schuko socket outlet with 1 RJ45 category 5e UTP brass Simon K45

REF. KSE15U/23/71



BASIC INFORMATION

DESCRIPTION

The mechanism-holder unit of the range Simon K45 range with manual closure and Schuko socket outlet with an RJ45 connector of category 5e. Supports the connection of an element of 16 up to 16 A of current and 250 volts. With these elements, the unit is designed to be installed quickly and very easily by insertion screw. The product is packaged in colour brass and can be installed in suspended floors or raised floor and concrete. In the case of installing it in concrete floor, you will need to also a specific tray for this type of floor (Ref. KGE1709), and in the case of the raised floor will be with its corresponding tray (ref. KGE170TF). The unit has dimensions of 130 x 130 millimetres and 55 millimetres of depth, and supports a cable section that is from 1.5 to 2.5 millimetres. The cover has a system reinforcing using anchor points that protecting the connections is used as long as its use of the possible damage due to the passage of personnel. The material used for its manufacture is metal and the unit is maintained on a thermoplastic baseboard, with all the advantages that this material provides as its self-extinguishing capacity in case of fire, and the minimization of toxic fumes.

FINISH

Brass

PACKAGING CONTENTS

IP66 brass mechanism-holder unit with manual lock, square sealing gasket for IP66 tray, 1 Schuko socket base, 1 category 5e RJ45 UTP connector, 4 screws for fastening the mechanism-holder unit and installation manual

ETIM CLASS

EC000024

MATERIAL

Metal

REMARKS

The cover has anchor points that protect the connections during use against pressures and stresses due to the passage of personnel.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, when the mechanism-holder unit is not in use, the cover can be hermetically sealed.

AVAILABLE IN

Empty IP66 brass mechanism-holder unit to complete with solutions from the K45 range, with socket plug and housing for an RJ45 connector, and combination of a socket plug with RJ45 connector

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal (1 input / 1 output)

NUMBER OF CONNECTORS

1

RJ45 CONNECTORS

Includes 1 RJ45 category 5e UTP connector

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

DUST SHUTTER

No

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07,08

INDICATOR FUNCTION

No

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

CURRENT (A)

16 A

IP RATING

IP66

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1000kg

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2 modules

RECESS DIMENSION (MM)

145 x 145 mm em chão falso

RJ45 ADAPTOR MODULE

Included with the mechanism-holder unit

SNAP-FIT RJ45 PLATES

Keystone I and II

SNAP-FIT TYPE

Keystone I and II

NUMBER OF SOCKETS

1 socket for standard current circuits

VERSION

1 element

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF FASTENING

The mechanism-holder unit is fitted to the tray using 4 x 2.5 mm hexagonal head screws (Allen type) supplied with the mechanism-holder unit.

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

INSTALLATION DIRECTION

The cover opens in the direction chosen according to the orientation of the tray during the installation phase.

INSTALLATION TYPE

Its design allows incorporation in any type of floor, be it a raised or a concrete floor, combining the mechanism-holder unit with the tray in accordance with the type of installation (ref. KGE170 for concrete floor, and ref. KGE170TF for raised floor)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

3 inputs / outputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-23:2008 +

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436048638

PRODUCT NET WEIGHT

0.445

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1445213

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436048638

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.445

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

77

PACKAGING NET WEIGHT

0.445

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

137

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.445

PACKAGING LENGTH

137