

German socket outlet 16A 250V~ with safety device and fast terminal connection champagne Simon 31

REF. 31464-64



BASIC INFORMATION

DESCRIPTION

Schuko socket outlet with safety device (as the covers include the child protection function) and quick terminal connection, in champagne colour and belonging to the series Simon 31. This socket-outlet has a current of 16 A and a voltage of 250V, in addition to a operation is by insertion. It has 2 modules and supports a section of wire 2.5 mm with a stripped 13 mm. Complies with the European standards and regulations UNE 20315-1-1: 2009, UNE 20315-1-2: 2009 and can be installed on surfaces with a temperature located between 5 and 40°C, approximately, although it's true that can withstand extreme temperatures of -25 to 50°C, plus or minus. Its dimensions are 64x65 mm and it is manufactured with metal components with halogen-free insulation and trim metallized thermoplastic. For a correct maintenance to this safe socket-outlet, it will only need to wipe it with a soft and dry cloth, without having to use abrasive cloths or cleaners that contain chlorine in its formula.

FINISH

Champagne

PACKAGING CONTENTS

Socket outlet with cover

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

MONOBLOCK

No

CABLE SECTION ADMITTED (MM)

2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko

TYPE OF MECHANISM

Insertion

VERSION

Single

INDICATOR FUNCTION

No

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLATION TYPE

Suitable for surface and flush
mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE 20315-1-1:2009, UNE 20315-1-2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.1

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053055670

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

3026595

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.995

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

83

PACKAGING NET WEIGHT

1

UNITARY PACKAGING GROSS
WEIGHT

0.1

PACKAGING WIDTH

165

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221