

Angled voice and data plate with dust cover for 1 element with 1 RJ45 category 6 FTP graphite Simon 500 Cima

REF. 50003081-038



BASIC INFORMATION

DESCRIPTION

Angled plate in graphite colour of the Simon 500 Cima series and that is used for both data and voice. It has dust cover with 1 element and 1 RJ45 category 6 FTP Keystone I, II, ATT ® / Avaya ®. This voice and data plate Simon 500 Cima includes all the necessary for that you can install it in enclosures horizontalen und vertikalten Verbindungen, without that you have to use a adapter for this purpose. It measures 50 x 50 x 55,4 mm and it is manufactured, according to the standard TIA 568 C. 2, with metal components with halogen-free thermoplastic (halogen-free, self-extinguishing), which is a material that promotes that does not occur propagate the fire, if a fire or a low level of toxicity if smoke. It works perfectly in places with a temperature between the -5 and 60 ° C and its cleaning is quite simple: Just wipe it with a soft and completely dry cloth.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with dust cover, RJ45 category 6 FTP connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097779

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.08

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.6

PRODUCT NET WEIGHT

0.08

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

