

Neutral push-button switch 10A 250V~ for half element with fast terminal connection system white Simon 27 Play

REF. 27659-64



BASIC INFORMATION

DESCRIPTION

Neutral push-button switch half element with quick terminal connection and finished in white colour of the Simon 27 Play series. This push-button switch with a voltage of 250V and an intensity of 10: 00 AM has a rocker operation and is suitable for installation both in surface-mounted and recessed in places with a temperature located between 5 and 40°C, although it can withstand extreme temperatures of between -25 to 50°C. It is fully compatible with the frames of the series Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua. There is the possibility of replacing the finish of the supplied rocker with 7 additional finishes that are available. It has 2 modules and supports a cable section of 1.5 to 2.5 mm, with a stripping of 11 mm. It has been manufactured in accordance with the standards EN 60669-1: 1999 + A1: 2002 + A2: 2008 + EN 50581: 2012 and is made of metal components with halogen-free thermoplastic fully halogen-free and the trim is made of thermoset material. To clean it, you have to do it with a soft, dry cloth without using never use abrasive cleaners or cloths with chlorine.

FINISH

White

MATERIAL

Thermoplastic

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000029

REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 5 additional finishes available.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 A

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small spaces and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252611

UNITARY PACKAGING HEIGHT

45.3

UNITARY PACKAGING WIDTH

36.7

UNITARY PACKAGING LENGTH

45.9

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.076

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.024

PRODUCT NET WEIGHT

0.02

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053044759

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

48.5

PACKAGING WIDTH

85.7

PACKAGING LENGTH

224.5

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.933

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.47

PACKAGING NET WEIGHT

0.4

PACKAGING WEIGHT UNIT

KGM