

Luminaire HOLE 110 Flush mount 3000K Flood White CRI98

REF. 91412932-300



BASIC INFORMATION

FINISH

White

APPLICATION

Flush mount

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

98

LUMENS (LM)

600 lm

IP RATING

IP20

DRIVER INCLUDED

No

LUMENS/W

600

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

Type 3

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

33 V~

L70 (°C)

150.000h at 25°C

OPTICS

Flood 35°

RAL

9016

L90 (°C)

40.000h at 25°C

POWER (W)

7.5 W

COLOR TEMPERATURE (K)

2700 K

LIGHTING EFFICIENCY (LM/W)

103 lm/W

SERVICE LIFE

50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

EAC MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547067206

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.58

PRODUCT NET WEIGHT

1.58

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8436547067206

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

180

PACKAGING WIDTH

215

PACKAGING LENGTH

350

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

13545000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.58

PACKAGING NET WEIGHT

1.58

PACKAGING WEIGHT UNIT

KGM