

Toxic/explosive gas detector for flush mounting with LED service status indicator white

REF. 75861-30



BASIC INFORMATION

DESCRIPTION

Toxic and explosive gas detector: Butane gas, propane gas and city gas (kitchens). It is white in colour and incorporates a service status indicator led. For operation it requires the power supply unit with reference number 75870-30. It incorporates a signal function with 0.9 W power consumption and is suitable for surface mounting or flush mounting. It works through an internal probe. It has a size of 8 x 32 mm and is compatible with 230 V voltage elements and a frequency of between 50 and 60 Hz. It is made of metal components with thermoplastic insulation and halogen-free. To clean it with a soft cloth moistened in soapy water and avoid abrasive cleaners containing chlorine. This product belongs to the Simon 75 series, a collection that stands out for the improvement of habitability, giving a precise response to the new demands of the current market.

FINISH

White

COMPATIBLE WITH SOLENOID VALVE

Yes

COMPATIBILITY

Frames Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations, Simon 28, Simon 31, Simon 44 Aqua, Simon 75, Simon 82 Detail, Simon 82 Nature, Simon 82 and Simon 88

PACKAGING CONTENTS

Gas detector and instruction sheet

ETIM CLASS

EC002455

REMARKS

Requires power supply ref. 75870-30.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FREQUENCY

50 - 60 Hz

OPERATING TEMPERATURE RANGE (°C)

0 - 40 °C

ACOUSTIC FUNCTION

Yes

INDICATOR FUNCTION

Yes

MODE OF OPERATION

Internal probe

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

POWER SUPPLY (V~)

230 V~

CONSUMPTION INDICATOR (MA)

0.9 W

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

COMPATIBLE WITH PROPANE GAS

Yes

NUMBER OF CONTACTS

4

STORAGE TEMPERATURE RANGE (°C)

-20 - 75 °C

NUMBER OF CONTROLLABLE CIRCUITS

1

COMPATIBLE WITH METHANE GAS

Yes

ENTRY FOR DETECTORS

No

COMPATIBLE WITH NATURAL GAS

Yes

VERSION

Single

NUMBER OF POSSIBLE ELEMENTS

1 element

NUMBER OF WIRES

4

INSTALLATION AND MAINTENANCE

COMPATIBLE WITH BUTANE GAS

Yes

CLAW

Included

INSTALLATION TYPE

Suitable for surface and flush mounting

CABLE STRIPPING NECESSARY (MM)

11

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

UNE-EN 61000-6-3:2007 + A1:2012

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053058459

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

329232

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.1

PRODUCT NET WEIGHT

0.1

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053058459

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

57

PACKAGING WIDTH

76

PACKAGING LENGTH

76

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

329232

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.1

PACKAGING WEIGHT UNIT

KGM