

Trim plate for 1 quick connection connector with 3 poles male or female for 1 element black Simon K45

REF. K18/14



BASIC INFORMATION

DESCRIPTION

Suitable for both surface-mounted and to be recessed and with an elegant finishes in black, our trim plate for one 3-pole quick connection connector is part of the collection Simon K45 to choose between male or female, its dimensions are 45x45x8,5 mm and is manufactured in halogen-free thermoplastic material to be able to ensure that the fire is not propagate if had fire, in addition to a minimum toxicity in the event of smoke generation. Although the piece does not include the connector, you can choose from other brands of fast-connection connectors, since our plate is compatible with the leading manufacturers. The only thing is required for proper fastening the connector is that the clips have between 1.5 and 2 mm in thickness. And it is that the collection Simon K45 has been specially designed to fall in love up to the most demanding clients, as it brings together all types of mechanisms self-extinguishing to be able to enjoy a total security. This is why our commitment by reinventarnos every day you Patent in each and every one of our collections.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Plate for one 3-pole quick connection connector

ETIM CLASS

EC000011

REMARKS

Connector not included (to be purchased separately). If using another quick connect brand, the plate is compatible with the leading manufacturers (Wieland®, Wago®, etc). To fix the connector to the plate correctly, the clips must be between 1.5 and 2 mm thick.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Versions for 1 and 2 quick-connection connectors with 3 male or female poles

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

GST18

INDICATOR FUNCTION

No

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

Half

RAL

7021

VERSION

Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE PLATE

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60535:2009 A1:2013

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.009

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436036703

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.18

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.18

UNITARY PACKAGING GROSS
WEIGHT

0.009

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140