Schuko socket outlet 16 A 250V~ with safety device and screw terminal connection white Simon K45

REF. **K01/9**



BASIC INFORMATION

DESCRIPTION

The socket outlet K01 / 9 socket of the series Simon K45 with safety device and 2 modules with screw connection with a few finishes white in colour, measuring 45x45 mm, our piece is manufactured with metal components with self-extinguishing thermoplastic insulation. This means that its materials are free of halogens and ensure that no flame spread in case of fire and low toxicity, providing a if had smoke. It is compatible with elements up to 250 Volt voltage and 16 Amps intensity. The series Simon K45 is the perfect solution for the most demanding, thanks to its constant innovation and the exhaustive compliance with applicable European standards to offer the best guarantee. At Simon, we concern that our products offer the highest security for your home.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Socket outlet with trim cover

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
1,5 to 2,5 mm

NUMBER OF CONNECTIONS PER TERMINAL
2 connections per terminal (1 input / 1 output)

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

FORMAT
Schuko

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION
No

INSULATION RESISTANCE (V-MΩ)
>5M? At 500 V

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 a 60° C

TYPE OF MECHANISM
Insertion

NUMBER OF MODULES
2 modules

MONOBLOCK
No

NOMINAL VOLTAGE (V~)
250 V~

RAL
9003

NUMBER OF SOCKETS
1

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
12

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE SOCKET
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

NUMBER OF TERMINALS
3 inputs / outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod.|EN IEC 63000:2018|IEC 60884-1 Ed. 3.2|UNE 20315-1-1:2017|UNE 20315-1-2:2017|DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053227565

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
121251

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.045

PRODUCT NET WEIGHT
0.045

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053122792

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
49

PACKAGING WIDTH
101

PACKAGING LENGTH
245

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1212505

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.51

PACKAGING NET WEIGHT
0.45

PACKAGING WEIGHT UNIT
KGM