

Kit Flash 60 consisting of schuko power socket end in Quick-connection connector white Simon 400

REF. 43101002-130



BASIC INFORMATION

DESCRIPTION

Kit based on schuko socket-outlet to be installed in furniture with an optional protective cover to allow for closure and conceal connections when not in use. This product is supplied in white finish, assembled and wired with a 20 cm long flexible cable ending in a male quick connect overhead connector of 3 poles type Wieland® GST8i with safety anchoring to facilitate safe connection and disconnection from the power network without the need to interrupt the power supply. The kit is supplied with the internal connections already made. It is only necessary to create the hole in the furniture where the product will be fasten and once done, connect it to the power supply to make it functional.

FINISH

White

MATERIAL

Plastic

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF CONTACTS

3

NOMINAL VOLTAGE (V~)

250 V~

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

FORMAT

Schuko

RAL

9003

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the socket-outlet against entry of dust and small objects

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

RECESS DIMENSION (MM)

ø54 mm

CURRENT (A)

16 A

RJ45 ADAPTOR MODULE

No

RJ45 CONNECTORS

No

IP RATING

IP20

SNAP-FIT RJ45 PLATES

No

CONNECTOR TYPE

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

No

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF THE FRAME

Only with tool

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REMOVAL OF CONNECTOR

No tools needed

SECURING POSSIBILITIES

Using supplied claws

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053292075

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053292075

PACKAGING VOLUME

544320

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

72

PACKAGING GROSS WEIGHT

0.136

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

72

PACKAGING NET WEIGHT

0.124

UNITARY PACKAGING GROSS
WEIGHT

0.136

PACKAGING LENGTH

105

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.124