Complete kit with cover, metal fin, 2 schuko socket outlets, 2 UPS socket outlets, plate for 2 RJ45 connectors black S400 Indesk

REF. **45502220-138**



BASIC INFORMATION

DESCRIPTION

The Simon 400 Indesk series is designed to offer solutions for the most demanding environments. Thanks to this series, we will have all the necessary connections within reach without the need for annoying cables on the floor. A complete kit with cover and fin, created to be flush-mounted into the table, has the capacity for 2 standard schukos, 2 for UPS, and a plate for two RJ45 connectors in black. The dimensions of this 5 element piece are 295 x 185 x 85 millimeters and it supports 250 volts and 16 amps of current. Its connection is made via a Wieland® gst18i figure three-pole male aerial connector with a 22-centimeter patch cord. Manufactured with high-quality materials that provide this piece with great resistance, an example of this is its painted steel enclosure, its anodized aluminum profile, its covers and mounting components in self-extinguishing thermoplastic and halogen-free.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with metal fin

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

RECESS DIMENSION (MM)
273 x 175 mm (± 2mm)

NUMBER OF RJ45 WINDOWS
2

SNAP-FIT RJ45 PLATES
Keystone I, II and Systimax

SNAP-FIT TYPE
Keystone I, II and Systimax

NUMBER OF SOCKETS
2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

NUMBER OF UPS SOCKET OUTLETS
2

VERSION
5 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
With metal fin

CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for recessed mount in furniture.

OPENING ORIENTATION
At 45º

SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053208380

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.15

PRODUCT NET WEIGHT
2.15

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053208380

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
300

PACKAGING WIDTH
195

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5265000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.15

PACKAGING WEIGHT UNIT
KGM