

Modular luminaire 720 Advance M4 120x30 Low Glare NW

REF. 72061040-684



BASIC INFORMATION

DESCRIPTION

With optics micro prismatic and system anti-deslumbramiento LowGlare, the luminaire 720 modular Advance M4 of the collection Simon for indoor lighting, the highest quality lighting with a style of finishes in white. This luminaire provides a light of a white neutral, with a colour temperature of 4000 K and 3400 lm for NW, with a consumption of luminaire 28 W. It, and thanks to the fact that it includes multiple LEDs low consumption, has a service life of 100,000 hours for the L70 at 25 ° C and 40,000 hours for the L90. Compatible with power Volt voltage 100-240 and 50-60 Hertz rate, with control system, switching on ON-OFF in a compact 120 x 30 mm This designed for installation in false ceiling and hardware, both flush mounted and surface-mounted, adapting to the needs technical and aesthetics of the space.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

121 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3400 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

On/Off

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191682

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191682

PACKAGING VOLUME

0.234

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

300

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.58

PACKAGING LENGTH

1200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5