

USB 2.0 connector type A for half element ivory Simon 27 Play

REF. 2701090-031



BASIC INFORMATION

DESCRIPTION

A good connection is the beginning of all electronic mechanism, without it nothing is possible. If we are talking about sockets, TV / RJ / Multimedia we find the half element USB 2.0 type-A included in the Simon 27 Play series, with an ivory finish and dimensions of 22.5x45 mm, has a number of pins and wires of five and is available in boxes of one unit, being one of the most demanded in the market today. Due to its features, the maximum recommended length of cabling is 5 meters for low-speed devices and 2.2 meters for high-speed devices. It has a screw terminal connection and a type of insertion operation, being suitable both for surface or flush mounting, in addition, it supports a wire section from 0.2 to 0.5 mm. Another advantage is the metal components with halogen-free insulation and thermoplastic trim with which it has been manufactured.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

USB female connector and instruction sheet

ETIM CLASS

EC000018

REMARKS

Recommended maximum cable length: 5 metres for low-speed devices and 2.2 metres for high-speed devices. For more information see the product instruction sheet.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

NUMBER OF CONNECTORS

1

CONNECTOR TYPE

USB

NUMBER OF CONTACTS

5

NUMBER OF POSSIBLE ELEMENTS

Half element

FORMAT

USB

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

NUMBER OF WIRES

5

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

5

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small spaces and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053090190

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.055

PRODUCT NET WEIGHT

0.055

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053090190

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

57

PACKAGING WIDTH

76

PACKAGING LENGTH

76

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.329

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.055

PACKAGING WEIGHT UNIT

KGM