

Downlight 725.23 Flush mount NW General Aluminium

REF. 72523033-984



BASIC INFORMATION

DESCRIPTION

The line Downlight 725.23 of the Company Simon, brings together all the conditions needed to achieve a brightness of 100% when switched on. This is due to Simon's extensive experience in the LEDs, which uses all its resources of research to be at the height of the highest quality in the market. This results in the long service life of the luminaire and the resulting saving in maintenance costs due to the fact that the LEDs are not changed often. This also guarantees minimal glare and high visual comfort. Its continuous flicker-free light avoiding visual fatigue and is suitable for places such as hotels, offices, hospitals, etc. This is the luminaire indoor lighting Downlight 725.23 flush-mounted. Colour temperature 3900 K NW Advance. General lighting. The light beam is sent to the bottom with an angle of 40°, which makes the vision of work areas. Category A 30,000 h at 25 ° C. 100-240 V 50 / 60 Hz. ON-OFF switching system with adjustment options of 1-10 V Weight 0.5 kg Material Aluminium. For flush mounting using an accessory. Dimensions 165x51 mm

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1300 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

1300 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

93 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.504

PRODUCT NET WEIGHT

0.504

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116814

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

195

PACKAGING LENGTH

195

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.042

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.504

PACKAGING WEIGHT UNIT

KGM