

Downlight 725.23 Flush mount NW General IP44 White

REF. 72523930-984



BASIC INFORMATION

DESCRIPTION

This product is part of the downlights of the range 725 Category A of the brand Simon, characterized by its high lighting capacities and high quality of materials. The Downlight 725.23 Advance provides a neutral light (NW) thanks to its optics GENERAL- IP44. Its dimensions of 165 x 51 millimetres and its traditional white colour make it capable of adapting to any room and place that you want to be lit. In addition, its size and easy installation by means of recessed in the wall or ceiling, makes it possible to combine with other products of lighting in the same features, according to the needs of the space where it is placed. It has a colour temperature of 3,900 K and, at 1300 lumens and 14 Watts, and its control is performed by the classic and effective system ON / OFF requires a power supply of 100-240 volts and 50 / 60 Hertz rate of frequency for proper operation. This downlight stands out for its high quality materials, which means that it can operate and light rooms, without losing efficiency, low temperatures very low and high, ranging from - 15 to 40 degrees centigrade.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1300 lm

IP RATING

IP44

ELECTRICAL CLASS

Type 1

LUMENS/W

1300 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

93 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053116890

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.616

PRODUCT NET WEIGHT

0.616

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116890

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

195

PACKAGING LENGTH

195

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.042

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.616

PACKAGING WEIGHT UNIT

KGM