

2-way switch with key 5A 250V~ (key removable in both pos.) and welding terminal connection system ivory Simon 31

REF. 31521-31



BASIC INFORMATION

DESCRIPTION

For the classic and also for the most modern. The colours of always and the most modern. Simon always thinks of all people, in the different needs and in the different tastes that exist. The Simon 31 series would not be an exception. This 2-way switch with key resists elements up to 5 Amps and 250 Volt voltage. It is equipped with 2 positions (key removable in both positions). It has welding terminal connection, being its installation very simple. A stylish ivory finish that fits with the colours of all kinds wall-mounted or room. Individual version with 1 element and 2 modules. This 2-way switch is made in various components (have halogen-free insulation and thermoplastic trim, its dimensions are 64x65 mm. If you need this piece but in a different design, please consult our online catalogue.

FINISH

Ivory

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and key is removable in both positions.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

KEY-REMOVAL POSITION

Both positions

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VOLTAGE (V~)

250 V~

CURRENT (A)

5 A

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.105

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

419050

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053007204

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

419050

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.105

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

58

PACKAGING NET WEIGHT

0.105

UNITARY PACKAGING GROSS

WEIGHT

0.105

PACKAGING WIDTH

85

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

85